Huber Latin America y Cia. Ltda.

HUBER Alimentación por Canal HLC (Launder Channel)

Feed system for screenings wash presses

- Wastewater or service water as flushing water
- Up to 30 m channel length
- High operating reliability, low maintenance requirements
- Customised solutions

The HUBER Launder Channel HLC operates discontinuously in a batch mode or continuously. The screenings to be treated drop into the launder channel from one or several screens. Wastewater or service water is used to flush the screenings into the wash press. The flushing water serves also as wash water for screenings washing.

HUBER Launder Channels can be adjusted to suit customer-specific requirements. To ensure maximum operating reliability the launder channel control system can be designed to use redundant wash press systems and operate the individual units as needed via according valve control.

Ventajas

- Cost-effective, low maintenance solution

- High operational reliability
- Up to 30 m channel length
- Wastewater or service water as flushing water
- Stainless steel design for corrosion resistance

Downloads

Folleto: Alimentación por Canal - Launder Channel (inglés) [pdf, 480 KB]

Casos prácticos

- Ingeniería de transporte de materiales de HUBER SE: ¡Imprescindible y fiable!
- A successful combination: Launder Channel plus Wash Press SL

Media

Video: HUBER Launder Channel HLC

https://www.youtube.com/watch?v=g-aczj1GDiY

Más productos de este grupo: Tratamiento de residuos de desbaste

- Prensa con lavado de residuo WAP®
- Prensa con lavado de residuo WAP® SL
- Prensa con lavado de residuo WAP® SL HP
- Screenings Wash Press WAP® L for Launder Channel Feeding
- HUBER Tornillos transportadores
- HUBER Screenings Compactor Ro7
- Lavado de residuo integrado

Huber Latin America y Cia. Ltda.
Eduardo Marquina 3937 of. 708
Vitacura, Santiago de Chile
Chile

Tel: +56 2 208 03 34

Email: info@huber-technology.cl
Internet: www.huber-technology.cl

Member of the HUBER group:
www.huber.de